



J A V E L I N

desktop card printers

Javelin™ Card Printers



**Card printers with professional performance at a perfect price!
Ideal for ID solutions and field-proven for financial/banking applications.**

The latest Javelin card printer range now consists of just two base models: J200i (for single card feeding) and J230i (with input hopper and output stacker). Both models print either in colour or monochrome, and a flipper is available for dual-side printing. These new Javelin card printers are reliable, compact and easy-to-use, delivering outstanding performance at a great price. Boasting a full range of encoding options, they are an economic, reliable solution for almost every card printing and encoding need.

Compact and Flexible

- Small footprint easily fits into a wide range of locations
- Conveniently fits on the desktop or under the counter
- Print in full colour or monochrome
- Flipper for dual-side printing (option)

Easy-to-Use

- User-friendly USB plug-and-play setup
- LCD screen displays printer status and diagnostics
- Easy to change ribbon and thermal print head
- RFID ribbon protection
- ATM style single-card feed
- Basic ID card software package included with each printer

Encoding and Network Options (for both models)

- 3-track magnetic stripe encoding (HiCo/LoCo)
- Contact and contactless smart card encoding capabilities
- Built-in 10/100 Ethernet for printer networking

Ideal for:

- Employee ID cards
- Student & faculty ID cards
- Access control cards
- Gift cards
- Financial cards
- Visitor ID cards
- Personalized member cards
- Loyalty cards
- Self-service kiosk applications

... and more!



Javelin J200i
Manual feed

Optional flipper unit



Javelin J230i
Auto feed

Output stacker





Javelin™ Card Printers at a glance



ADD JAVELIN5™ INTUITIVE CARD DESIGN SOFTWARE
Javelin5 is a multifunctional software application that offers easy and flexible features to manage any card design and printing need. From the back office card production to the low-end personalization solution, Javelin5 offers the easy-to-use solution with total control of your options.



EMV INSTANT ISSUANCE SOFTWARE
Couple your Javelin with Xpressi™ software for an EMV instant card issuance solution that is cost-effective and easy to implement. Supporting multiple EMV configurations, chip types and even printer brands with one system, this solution gives an issuer the flexibility to keep their future expansion and operation options open for change.

Genuine NBS Supplies
Your choice of card printer supplies is critical. It is a primary factor affecting the reliability and consistency of printing. Genuine Javelin supplies meet stringent quality standards and are tested for optimum performance with Javelin card printers.



For further detail on any of the above products, please consult the corresponding NBS brochure.



J200i



J230i

Print

• Print Method	Thermal transfer (mono), Dye-sublimation (colour)
• Print Speed	mono: 6 sec/card, YMCKO: 26 sec/card (single-side) YMCKOK: 38 sec/card (dual-side)
• Print Mode	Single-side printing (option: dual-side printing)
• Resolution	300dpi (11.8 dpm), 16.7 million colours
• Ribbons	KrO: 500 prints/roll, YMCKO: 200 prints/roll, YMCKOK: 167 prints/roll, Half-panel YMC plus full-panel KO: 300 prints/roll Monochrome: black, silver, gold, red, blue, white: 1000 prints/roll

Card

• Card Types	PVC, composite PVC
• Card Thickness	0.5mm - 1.2mm; 20mil - 50mil
• Card Format	ISO CR-80-ISO 7810: 53.98mm (W) x 85.60mm (L) / 3.375" x 2.125"

Encoding (option)

• Magnetic Stripe	ISO7811 (tracks 1, 2, 3); Hi-Co/Lo-Co Head life - 4,000,000 passes
• Contact (IC)	ISO 7816, EMV, PC/SC IC contact life : 1,000,000 passes
• Contactless (RF)	MiFare, ISO 14443 A,B, ISO15693

Network (option)

• Ethernet(TCP/IP)	Built-in Ethernet (10/100 Mbps)
--------------------	---------------------------------

Other

• Barcodes	Code 39, Code 128 B & C with & without check digit, 2 of 5 interleaved, UPC-A, EAN 8 & EAN 13 PDF-417 2D bar code and other symbols can be printed via Windows® drivers
• Fonts	True Type fonts via Windows drivers
• CPU	32 bit processor
• RAM	16 MB
• Interface	USB2.0, RS-232C, network (option)
• Printer Driver	Windows 2000, XP, Server 2003/2008, Vista, Windows 7
• Printer Warranty	2 years

Feeding Method

• Single Feeding	yes	yes
• Auto Feeding	no	Input hopper: 100 cards; Output stacker: 70 cards

Temperature

• Operating Temperature	0 - 50°C / 32 - 122°F, 20 - 90% RH
• Storage Temperature	-25 - 70°C / -13 - 158°F

Power

• Adaptor	Input: 100V - 250V, 50/60Hz; Output: DC 24V
• Approvals	FCC Class B, CE and UL & CUL approved

Size

• Dimensions	Single side: 292mm (L) x 196mm (H) x 192mm (W) 11.5" x 7.7" x 7.6"	Single side: 403mm (L) x 202mm (H) x 192mm (W) 15.8" x 8.0" x 7.6"
	Dual side: 359mm (L) x 196mm (H) x 192mm (W) 4.1" x 7.7" x 7.6"	Dual side: 471mm (L) x 202mm (H) x 192mm (W) 18.5" x 8.0" x 7.6"
• Net Weight	Single side: 4.5 kg / 9.9 lbs Dual side: 5.0 kg / 11.0 lbs	Single side: 5.5 kg / 12.1 lbs Dual side: 6.0 kg / 13.2 lbs



Easy to change ribbon and print head



Consumables



Website: www.nbstech.com
Email: info@nbstech.com

Corporate Headquarters
Canada
703 Evans Avenue
Toronto, Ontario
M9C 5E9
Canada
tel: +1 416.621.1911
fax: +1 416.621.8875

Contact your nearest NBS location for more information on Javelin card printers & consumables:

Europe, Middle East, Africa
B1 Moorfield Point
Slyfield Industrial Park
Guildford, Surrey GU1 1RU
United Kingdom
tel: +44 (0)1483 563200
fax: +44 (0)1483 511189

North / South America
10925 Bren Road E
Minneapolis, MN 55343
USA
tel: +1 416.840.8620
fax: +1 952.912.9439

Asia Pacific
PO Box 780
Hurstville BC
NSW 1481
Australia
tel: +61 (2) 9546 6841
fax: +61 (2) 9546 6851

©Oct 2010 NBS Technologies Inc. Specifications are subject to change without notice. All rights reserved. NBS and the NBS logo are registered trademarks of NBS Technologies Inc. in the United States and Canada and are trademarks in other countries. Javelin and the Javelin logo are registered trademarks of NBS Technologies Inc. in the United States and European Union and are trademarks in other countries. Xpressi is a trademark of NBS Technologies Inc. with registration pending or completed in Canada, European Union, Chile and Peru. Javelin5 and the Javelin5 design are trademarks of NBS Technologies Inc. All other brand and product names are the trademarks or registered trademarks of their respective holders.