



# Javelin J330i

## The new face of card printing reliability

The next generation of our most popular card printer, the Javelin J330i is one of the most powerful and flexible card printers in its class. Easy to use, this single-sided card printer produces reliable and high performance printing at an affordable price.

Use the Javelin J330i card printer for:

- Corporate ID cards
- Student and faculty IDs and access control cards
- Membership and club cards for retail and warehouses
- Hospital staff and patient IDs

## **Reliable Operation**

- Newest generation of the highly reliable J300 series
- Revolutionary angled card feeder design\*

## **Powerful**

- LCD display
- Translucent card feeder and print viewing
- Print head bracket opens wider for easy ribbon loading
- Gentle open & close print head latch

### **Flexible**

- 16 Mb memory standard
- Optional built-in Ethernet connectivity
- Contact and contactless smart chip encoding options

... big performance at an affordable price ...





## Javelin<sup>®</sup> J330i Technical Details

## **Features**

- 25 Sec/Card Full Colour Print Speed
- USB or USB with Built-in Ethernet
- 100 card capacity feeder (220 high capacity feeder option)
- LCD for immediate printer status
- i-Series Printers require the use of TrueColours™ i-Series ribbons for full colour printing

#### **GENERAL SPECIFICATIONS**

- · High speed printing
- · 16Mb image memory standard
- · Card feeder capacity: 100 cards (30 mil)
- Card output hopper capacity: 100 cards (30 mil)
- Windows® drivers for XP, Vista, 2000 & Server 2003
- · Bi-directional driver communication
- · Up to three years printer warranty
- · Up to two years (unlimited passes) print head warranty

#### PRINTING

- · Colour dye sublimation or monochrome thermal transfer printing
- 25 seconds per card full colour single-sided (YMCKO)
- 4 seconds/card for resin black (K)
- 300 dpi (11.8 dots/mm) print resolution

#### BAR CODES

- · Code 39, Code 128 B & C with & without check digit
- · 2 of 5 & 2 of 5 Interleaved
- UPC-A, EAN 8 & EAN 13
- PDF-417 2D bar code and other symbologies can be printed via Windows drivers

#### **CARD SPECIFICATIONS**

- Types: PVC, PVC Composite, Adhesive backed
- Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- · Magnetic Stripe-ISO 7811
- Smart Card-ISO 7816-2
- Card thickness: 10 mil (.25mm) to 60 mil (1.524mm) (+/- 10%)

#### **RIBBON SPECIFICATIONS**

Javelin i-Series printers require the use of Javelin encoded i-Series ribbons for full colour printing

- Monochrome: Black 1000 & 1500 cards/roll
- Monochrome: 1000 cards/roll: blue, red, green, silver, gold, white and scratch-off grey (840 cards/roll)
- YMCKO: 200 & 330 cards/roll
- 1/2 panel YMC full KO: 450 cards/roll
- · KdO: 500 cards/roll
- · KrO: 500 cards/roll
- Overlay varnishes: Clear and Hologram: 350 cards/roll

#### **COMMUNICATIONS INTERFACE**

- · USB 1.1 (cable included)
- Built-in Ethernet (option)

#### MECHANICAL

- Width: 18.2 in (462mm)
- Depth: 9.4 in (239mm)
- · Height: 10.1 in (256mm)
- Weight: 15.5 lbs (7.0kg)

#### **ELECTRICAL**

- 110 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- FCC Class B, CE, UL and CUL approved

### ENVIRONMENTAL

- Operating Temperature: 60°F to 86°F (15°C to 30°C)
- · Operating Humidity: 20% to 65% non-condensing
- Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- Storage Humidity: 20% to 70% non-condensing
- · Ventilation: Free air

#### OPTIONS

- · Built-in Ethernet
- Smart card personalization: contact and contactless (30 mil cards only)
- · Magnetic encoder (30 mil cards only) 3 track HiCo/LoCo
- · Cleaning supplies
- High capacity feeder (220 cards)

Microsoft, Windows, and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.





