

# **Kiosk Card Printer**

from NBS Technologies


## Javelin<sup>®</sup> Kiosk

The NBS Multiple Hopper Kiosk card printer is designed for applications requiring self-service instant issuance of personalised plastic cards. With up to 8 hoppers the NBS Kiosk is flexible with easy integration to create a cost effective and innovative kiosk.

NBS Kiosk offers an all in one solution with high quality full colour and monochrome printing single or dual sided with included reject function to retrieve defective and uncollected cards. The kiosk is also fully supported for any requirement of encoding. The high capacity and flexible multi hopper options minimise maintenance cost and time and maximise the kiosk application.

The metal structure and dust protection cover make this unit not only very robust and durable but also extremely reliable with a low cost of ownership.





### IDEAL FOR INSTANT ISSUANCE OF BANK CARDS, MEMBERSHIP CARDS, LOYALTY OR GIFT CARDS, TRANSIT CARDS, STUDENT CARDS, PREPAID CARDS, CASINO/GAMING CARDS

### THE JAVELIN® KIOSK OFFERS THESE KEY FEATURES AND BENEFITS:

## FLEXIBLE

- Single and multi tray hopper options
- 3 x capacity of card hopper 150, 250 or 500 cards
- Supports multiple encoding options
- Ethernet as standard

### CONSULTING

SOFTWARE



High volume card printing and

Metal structure

dispensing

Dust protection cover

### EASY-TO-USE

- Detachable card hoppers
- Low card alert
- LCD display for print status
- One USB interface
- Software package Driver, DLL, Data Transmission Protocol

HARDWARE SMA

SMART CARD MANUFACTURING



WWW.NBSTECH.COM


## Javelin<sup>®</sup> Kiosk


### **Printer Specifications**

Print Mode	Single or dual sided, unit is dual sided as standard
Print Method	Thermal transfer (mono), Dye-sublimation (colour)
Print speed	Mono: 6 sec/card, YMCKO: 23 sec/card (single-side) YMCKOK: 31 sec/card (dual-side)
Ribbons	KrO: 500 prints/roll, YMCKO: 250 prints/roll, YMCKOK: 170 prints/roll,
	Half-panel YMC plus full-panel KO: 400 prints/roll
	Monochrome: black, silver, gold, red, blue, white, scratch-off: 1000 prints/roll
Card encoding options	Magnetic Stripe: ISO7811 (tracks 1, 2, 3); Hi-Co/Lo-Co, Head life - 4,000,000 passes
	Contact (IC): ISO 7816, EMV, PC/SC, IC contact life: 1,000,000 passes
	Contactless (RF): MiFare, ISO 14443 A,B, ISO15693
Warranty	12 months
Printer interfaces	USB 2.0; internal USB hub to connect peripheral devices; built-in Ethernet (10/100Mps) network
Software drivers	Windows 2000, XP, Server 2003/2008, Vista, Windows 7, Windows 8
Fonts/Images	300 dots per inch (11.8 dots per mm) resolution, 16.7 million colours
	True Type fonts via Windows drivers
Barcodes	Code 39, Code 128 B & C with & without check digit, 2 of 5 interleaved, UPC-A, EAN 8 & EAN 13 PDF-417 2D barcode and other symbols can be printed via Windows <sup>®</sup> drivers
Card capacity	150 – 4000 cards depending on configuration each hopper capacity 150,250, 500 cards
Power source	Input: 100V - 240V, 50/60Hz; Output: DC 24V (FCC Class B, CE and UL & CUL approved)
CPU & RAM	CPU: 32 bit processor RAM: 128MB
Environment	Operating temperature: 0 - 50°C / 32 - 122°F, 20 - 90% RH
	Storage temperature: -25 - 70°C / -13 - 158°F

### **Card Specifications**

Types	PVC & composite PVC
Card width/length	ISO CR-80-ISO 7810: 53.98mm (W) x 85.60mm (L)
Card thickness	0.5mm - 1.2mm





Multiple Card Hoppers- 2/4/8 hoppers

**Removable Card Hoppers** 



w: www.nbstech.com e: info@nbstech.com Corporate Headquarters Canada 703 Evans Avenue Toronto, Ontario M9C 5E9 Canada tel: +1 416.621.1911

tel: +1 416.621.1911 fax: +1 416.621.8875 Contact our NBS card personalization experts for full details on this and other card personalization products at:

Europe, Middle East, Africa B1 Moorfield Point Slyfield Industrial Park Guildford, Surrey GU1 1RU United Kingdom tel: +44 (0)1483 563200 fax: +44 (0)1483 511189

North / South America 10925 Bren Road E Minneapolis, MN 55343 USA tel: +1 416.840.8620 fax: +1 952.912.9439 Asia Pacific PO Box 780 Hurstville BC NSW 1481 Australia tel: +61 (2) 9546 6841 fax: +61 (2) 9546 6851

RoHS

©March 2014 NBS Technologies Inc. Specifications are subject to change without notice. All rights reserved. NBS and the NBS logo are registered trademarks of NBS Technologies Inc. in the United States and Canada and are trademarks in other countries. Advantage and SmartSys are trademarks of NBS Technologies Inc. Xpressi & the Xpressi design are trademarks of NBS Technologies Inc. with registration completed or pending in Canada, the European Union, Peru and Chile. All other brand and product names are the trademarks or registered trademarks of their respective holders.